## ODU AMC<sup>®</sup> HIGH-DENSITY STRAIGHT PLUG, SIZE 1, IP6K8 / IP6K9K, 27 CONTACTS, A (LIGHT BROWN) KEY



Part number
 A11WAM-P27XBC0-0000

Type of connector Straight plug


• Size Size 1

Number of contacts 27

Keying
 A (light brown)



#### **DIMENSIONS:**







### **Contact Insert Description**

Number of contacts 27
Contact type Pins
Contact diameter 0.3 mm
Insulator material PEEK
Wire cross section 28 AWG
Termination type Soldercup

Data transmission HDMI 1.3 (8.13 Gbit/s)

Reverse gender on request

# ODU AMC<sup>®</sup> HIGH-DENSITY STRAIGHT PLUG, SIZE 1, IP6K8 / IP6K9K, 27 CONTACTS, A (LIGHT BROWN) KEY



#### **Technical information**

Nominal current single contact 1 A IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003)

Test voltage 0,75 kV AC EIA-364-20F:2019-02

5000

All shown connectors are rated to a safety extra low voltage (SELV) of less than 50 V AC / 75 V DC, according to IEC 61140:2016 (VDE 0140-1:2016) Protection against electric shock - Common aspects for installation and equipment. In case other standards rule a specific use of the connector, the application specific safety criteria shall be considered first. In this context, lower voltage ratings may be valid. Warning: Danger to life for operating voltages above 50 V AC / 120 V DC!

#### Mechanical and Environmental data

Degree of protection\* IP6K8 / IP6K9K Operating temperature -51°C - 125°C

Mating cycles
\*mated condition

\*mated condition

#### **Material and Surface Treatments**

Housing Cu-alloy with ruthenium finish
Contact Cu-alloy with gold finish

#### **General information**

All shown connectors are defined without breaking capacity (COC) according to IEC 61984:2008 (VDE 0627:2009).

The respective selected ODU connectors with data transfer functionality can transmit common data transmission such as HDMI<sup>®</sup> 2.0, USB<sup>®</sup> 3.2 Gen 1x1, FireWire<sup>®</sup> and eSATA<sup>®</sup>, but they are not HDMI<sup>®</sup>-, USB<sup>®</sup>-, FireWire<sup>®</sup>- and eSATA<sup>®</sup>-standard connectors.

ODU reserves the right to make changes based on the current state of knowledge without prior notice without being obliged to provide replacement deliveries or refinements of older designs.