




ODU
A PERFECT ALLIANCE.

-

Technical drawing of the AF 10 connector. The drawing shows a side view of the connector with various dimensions. The main body has a diameter of Ø15.5. The front flange has a diameter of Ø10.0 and a thickness of 3.5. The rear flange has a diameter of Ø15.0 and a thickness of 3.0. The total length of the connector is 15.5. The distance from the front flange to the rear flange is 11.5. The distance from the rear flange to the end of the connector is 6.5. The connector is labeled 'AF 10'.



Technical drawing of a hexagonal nut. The drawing shows a hexagonal shape with rounded corners. The dimensions are given as $10.1^{+0.1}$ for the width across the flats and $\varnothing 11.1^{+0.1}$ for the inner diameter.

252904

ODU AMC[®] REAR PANEL MOUNT RECEPTACLE, SIZE 0, IP6K8 / IP6K9K, 4 CONTACTS, A (LIGHT BROWN) KEY



Technical information

Nominal current single contact	5 A	IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003)
Test voltage	0,9 kV AC	EIA-364-20F:2019-02

All shown connectors are rated to a safety extra low voltage (SELV) of less than 50 V AC / 75 V DC, according to IEC 61140:2016 (VDE 0140-1:2016) Protection against electric shock - Common aspects for installation and equipment. In case other standards rule a specific use of the connector, the application specific safety criteria shall be considered first. In this context, lower voltage ratings may be valid. Warning: Danger to life for operating voltages above 50 V AC / 120 V DC!

Mechanical and Environmental data

Degree of protection*	IP6K8 / IP6K9K
Operating temperature	-51°C - 125°C
Mating cycles	5000
*mated condition	

Material and Surface Treatments

Housing	Aluminum with ruthenium finish
Contact	Cu-alloy with gold finish

General information

All shown connectors are defined without breaking capacity (COC) according to IEC 61984:2008 (VDE 0627:2009).

The respective selected ODU connectors with data transfer functionality can transmit common data transmission such as HDMI[®] 2.0, USB[®] 3.2 Gen 1x1, FireWire[®] and eSATA[®], but they are not HDMI[®]-, USB[®]-, FireWire[®]- and eSATA[®]-standard connectors.

ODU reserves the right to make changes based on the current state of knowledge without prior notice without being obliged to provide replacement deliveries or refinements of older designs.